



Shenzhen Xinghongtu Electronic Material Co.,Ltd.

Add: B16-3, No. 4, Ligang South Road, Bogang Community, Shajing Street,
Baoan District, Shenzhen, Guangdong, 518104, China
Tel: 0086-0755-81778348 Fax: 0086-0755-81778190
Email : sunny@xhttape.com

1. Product name : Double sided foam tape

2. Tape composition



3. Technical parameters

| Test items | Physical property | Test value |
|--------------------------------------|-------------------|------------|
| Total thickness | 870±20µm | 862 |
| Base material thickness | 0.8mm | 0.8mm |
| Initial Tack(positive) | ≥10# | 16# |
| Initial Tack(negative) | ≥10# | 15# |
| 180° Peeling Force (g/25mm) positive | ≥1200g/25mm | 1516g/25mm |
| 180° Peeling Force (g/25mm) negative | ≥1200g/25mm | 1572g/25mm |

1. 25mm wide tape stick on steel plate is rolled with a 2KG roller for 3 times and placed for 20min for test.

2. This technical data is based on the limited value of the product trial production period for reference, do not make the specification guarantee of the product.

3. For customer's specific application, please test and confirm in advance.

4. For the best adhesive effect, the adhesive surface must be clean and dry. When adhesive tape is stick on the surface, apply an average pressure of 2.0kg/cm² to the roller

5. above pressure, pressing time 3-5 seconds, so that it is effectively fitted, placing time more than 24h, to achieve the best bonding effect.

6. Adhesive force and retention force are tested by 50 μ m PET transfer test, the test speed: 300mm/min

7. Best storage conditions and use environment: temperature 6-30 ($^{\circ}$ C), humidity 0-85%, quality guarantee period: 6 months after purchase.

8. If the best storage conditions are not reached, long-term in direct sunlight, high temperature (above 40 $^{\circ}$ C), high humidity (above 70%RH), low temperature (below 0 $^{\circ}$ C), and other conditions, no 3 month guarantee.

Remarks: The above data is for reference only, no acceptance criteria. According to different test methods, the data are different. It is recommended that customers choose their own evaluation before choosing the appropriate product. This information with the product is not updated regularly, please refer to our latest edition, Please refer to the latest edition.